



WALLBOX ENTITY PRO 22 MID

Entity PRO complet wallbox with following components: An installation bracket, a chargin and a front panel. Available for purchase in a single or dual version. Entity PRO comes with a fixed cable available in various lengths or an outlet. Built-in electronic meter or visible MID meter. Integrated residual current device (RCD) with an all-pole mechanical circuit breaker for AC and DC that meets all requirements. The wallboxes can communicate with each other over Ethernet or mesh Wi-Fi and the internet over LTE CAT M1, Ethernet or Wi-Fi. NB: Complete wallbox.Charging station Entity Pro 22kW with outlet, phasebalancing, visible meter MID and modem with SIM for Garo Connect

E-number	Article number
2701003	354203

General properties

Type designation	EPCSO00332SVGI
Materials	Plastic
Colour	Black
Rated voltage [V AC]	230/400
AC/DC output	Type2 outlet
Package size [pcs]	1
Standard	EN61851-1, IEC62955, IEC61439-7, EN61008-1, EN60898-1, ISO15118
Frequency [Hz]	50
Temperature range [C]	-40C...+40C
Mounting method	Wall mounting
Degree of protection [IP]	54
Storage temperature [C]	-40C...+40C
RFID	Yes
Impact strength	IK10
Locks	Yes
Short-circuit current [kA]	10
RAL-nummer	RAL9011

Specific properties

Name	WALLBOX ENTITY PRO 22 MID
E-number	2701003
Article number	354203
Rated current [A]	32
Meter	Visible meter
Cable [m]	Not included
Netweight [kg]	4.20
Width [mm]	240
Height [mm]	340
Depth [mm]	150
Phases	3
Charging current [A]	0-32
Effekt [kW]	22